




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 11/06	A1	(11) International Publication Number: WO 98/55060 (43) International Publication Date: 10 December 1998 (10.12.98)
<p>(21) International Application Number: PCT/US98/11738</p> <p>(22) International Filing Date: 5 June 1998 (05.06.98)</p> <p>(30) Priority Data: 60/048,849 6 June 1997 (06.06.97) US</p> <p>(71) Applicant (for all designated States except US): ECHLIN, INC. [US/US]; 100 Double Beach Road, Branford, CT 06405 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): KUMAR, Satyendra [IN/US]; Apartment 108, 931 Century Drive, Troy, MI 48083 (US). KUMAR, Devendra [IN/US]; Apartment 108, 931 Century Drive, Troy, MI 48083 (US). DOUGHERTY, Michael, L., Sr. [US/US]; 2255 Greenbriar Drive, Rochester Hills, MI 48306 (US).</p> <p>(74) Agent: COLLINS, Robert, C.; Barnes, Kisselle, Raisch, Choate, Whittemore & Hulbert, P.C., 3500 Penobscot Building, 645 Griswold, Detroit, MI 48226-4217 (US).</p>	<p>(81) Designated States: AU, CA, DE, GB, JP, KR, MX, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>	

(54) Title: SUPPRESSION OF FLUID-BORNE NOISE



(57) Abstract

Apparatus for suppressing fluid-borne noise in a fluid conduit (12 or 12a) that includes a vibration sensor (36, 36a or 36b) for operative coupling to the conduit for providing an electrical sensor signal as a function of fluid pressure fluctuations in the conduit. A piezoelectric actuator (40, 40a or 40b) is adapted to be mounted on the conduit for imparting pressure fluctuations to fluid in the conduit. An electronic controller (38, 38a or 38b) is responsive to the sensor signal for energizing the actuator 180° out of phase with fluid pressure fluctuations sensed by the sensor. The sensor may be either closely coupled to the actuator, or separate from the actuator and disposed upstream of the actuator with respect to the direction of fluid flow through the conduit. The sensor in the preferred embodiments of the invention comprises a piezoelectric sensor, and the actuator comprises a stack of piezoelectric elements.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MM	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SUPPRESSION OF FLUID-BORNE NOISE

The present invention is directed to suppression of fluid-borne noise in fluid handling systems, such as in automotive power steering, power brake, fuel and air conditioning systems.

Background and Objects of the Invention

5 There are many applications in commerce and industry in which it is desirable to suppress fluid-borne noise in fluid handling systems. For example, in automotive applications, it is desirable to suppress fluid-borne noise generated by the pump or load in power steering, fuel distribution, air conditioning and power brake fluid systems. It is also desirable to suppress compressor noise in domestic and commercial air conditioning systems.

10 Fluid-borne noise can also be a problem in industrial hydraulic applications in terms of both generation of audible noise, and wear and fatigue of system components.

 Kumar, "Smart Materials For Acoustic or Vibration Control," Pennsylvania State University (1991) teaches that fluid-borne noise within a metal tube can be suppressed by positioning a piezoelectric actuator at one end of the fluid tube. The piezoelectric actuator

15 is disposed between an aluminum block that is affixed to the tube and an aluminum block that is coupled to a rubber membrane in contact with the fluid. A sensor is disposed between the actuator and the membrane block, and is coupled through a frequency selective preamplifier, a phase shifter and an amplifier for energizing the piezoelectric actuator 180° out of phase with the predominant frequency of vibration within the fluid.

20 Although the subject matter taught by the Kumar thesis addresses problems theretofore extant in the art, further improvements remain desirable. For example, an important consideration in high-volume applications, such as automotive applications, is that

the unit be economical to manufacture and reliable over an extended operating lifetime. One object of the present invention is to provide a system and method that satisfy these objectives. Another object of the present invention is to provide a system and method of fluid-borne noise suppression in which a single unit configuration can be employed in a variety of applications. For example, in one implementation of the invention, it is an objective of the invention to provide a system and method for suppression of fluid-borne noise in automotive power steering systems in which a single unit design can be employed in conjunction with a wide variety of power steering systems. Another object of the present invention is to provide a system and method that are characterized by low power consumption.

10 Summary of the Invention

Apparatus for suppressing fluid-borne noise in a fluid conduit in accordance with the various preferred embodiments of the invention includes a vibration sensor for operative coupling to the conduit for providing an electrical sensor signal as a function of fluid pressure fluctuations in the conduit. A piezoelectric actuator is adapted to be mounted on the conduit for imparting pressure fluctuations to fluid in the conduit. An electronic controller is responsive to the sensor signal for energizing the actuator 180° out of phase with fluid pressure fluctuations sensed by the sensor. The sensor may be either closely coupled to the actuator, or separate from the actuator and disposed upstream of the actuator with respect to the direction of fluid flow through the conduit. The sensor in the preferred embodiments of the invention comprises a piezoelectric sensor, and the actuator comprises a stack of piezoelectric elements.

The electronic control unit is responsive to frequency components of pressure fluctuations of fluid in the conduit for energizing the actuator as a function of the amplitude of the frequency component of greatest amplitude. The sensor is responsive to fluid pressure

fluctuations in the conduit over a broad frequency range, much lower than the resonant frequencies of the sensor and actuator. The frequency range in the preferred embodiments of the invention preferably is from zero to at least 1000 hertz.

5 A fluid handling system in accordance with another aspect of the present invention includes a conduit for conducting fluid under pressure and an apparatus of the character described above for suppressing fluid-borne noise caused by fluid pressure fluctuations in the conduit. In various embodiments of the invention, the conduit includes a volumetric enlargement to which the sensor and actuator are coupled, or a right-angled turn at which the sensor and actuator are disposed in opposition to fluid flowing through the
10 conduit. In another embodiment of the invention, the actuator comprises a plurality of annular discs disposed within the conduit in such a way that fluid flows through the discs. The sensor is either closely coupled to the actuator, or is separate from the actuator and disposed upstream of the actuator with respect to the direction of fluid flow through the conduit. In one preferred embodiment of the invention, the conduit includes an opening, and the noise suppression
15 apparatus of the invention is disposed in a unitary assembly removably received in the opening.

In accordance with yet another aspect of the present invention, a method of suppressing fluid-borne noise caused by pressure fluctuations in fluid flowing through a conduit includes sensing the amplitude and frequency components of pressure fluctuations in the conduit, and energizing a piezoelectric actuator as a function of the amplitude and
20 frequency components so as to impart pressure fluctuations to fluid in the conduit. The actuator preferably is energized as a function of the frequency component of greatest amplitude, 180° out of phase with such frequency component.

Brief Description of the Drawings

The invention, together with additional objects, features and advantages thereof, will be best understood from the following description and the accompanying drawings in which:

5 FIG. 1 is a schematic diagram of a fluid handling system equipped with a fluid-borne noise suppression apparatus in accordance with the present invention;

FIG. 2 is a schematic diagram of the noise suppression apparatus of FIG. 1; and

FIGS. 3, 4, 5 and 6 are schematic diagrams of respective modified embodiments of the invention.

Detailed Description of Preferred Embodiments

10 FIG. 1 illustrates a fluid handling system 10 in accordance with one implementation of the present invention as comprising a tubular section of conduit 12 that receives fluid at one end from a pump 14 and a sump 16, and delivers fluid from the opposing end through a load 18 to sump 16. Conduit 12 may be of any suitable composition. A collar
15 20 of low carbon steel or other suitable composition is affixed to conduit 12 between its opposed ends. As best seen in FIG. 2, collar 20 cooperates with conduit 12 to form a fluid volume 22 of enlarged diameter as compared with the diameter of conduit 12. An electronic assembly 24 has a case 26 with a plug 28 at one end adapted to be removably received within an opening 30 on collar 20. For example, plug 28 may contain external threads for removable
20 receipt within internally threaded opening 30. Alternatively, plug 20 and opening 30 may contain suitable fittings for quarter-turn mounting within the collar opening. Electronic assembly 24 is coupled to a source 32 of electrical power, preferably through a switch 34 for selectively applying power to assembly 24 during periods of use. For example, switch 34 may

be associated with an automobile power system for applying electrical power to assembly 24 during periods when the vehicle is in use.

Referring to FIG. 2, electronic assembly 24 in this embodiment of the invention includes a vibration sensor 36 that provides an input signal to a broad-band amplifier 38 as a function of fluid-borne vibration within area 22 of fluid conduit 12. The output of amplifier 38 is coupled to a piezoelectric actuator 40, which may comprise a stack of individual piezoelectric disks 42 as shown. Sensor 36 provides to amplifier 38 a signal having one or more frequency components associated with the frequency components of vibrations carried by fluid flowing through collar 20. Amplifier 38 is automatically responsive to the signal from sensor 36 for energizing actuator 40 as a function of the amplitude of the highest-amplitude frequency component of the input signal from sensor 36. Thus, actuator 40 is energized in direct proportion to the noise signal component of highest amplitude. Furthermore, amplifier 38 shifts such frequency component 180° , so that actuator 40 is energized 180° out of phase with the selected noise component. Thus, simply stated, actuator 40 imparts vibrations to the fluid within collar volume 20 at a frequency and magnitude to cancel or suppress the fluid-borne vibration wavelength of highest magnitude. Enlarged volume 22 enlarges the fluid surface area available for actuator 40. Sensor 36 and actuator disks 42 may be of any suitable composition, such as lead-zinc-titanate or modified lead-titanate. Piezoelectric actuators have several advantages including precision displacement, generation of large forces, extremely fast response, and high input impedance requiring low drive power. Amplifier 38, illustrated functionally in the drawings, may comprise simple analog circuitry, or digital circuitry based upon individual component or microprocessor control. Microprocessor-based control can employ fuzzy logic or neural network technology, if desired.

It will be appreciated, of course, that actuator 40 need not be disposed at a position directly opposite to the direction of fluid flow. The noise vibrations within the fluid create hydrostatic pressure pulses in all directions. Furthermore, a single sensor 36, broadband amplifier 38 and actuator 40 may be employed in a variety of applications in which fluid-borne noise is generally within the same frequency range. For example, fluid-borne noise in automotive power steering applications can be expected to be within the range of about 0 to 1000 Hz regardless of manufactures or model. This is well below the resonant frequency of typical sensors 36 and actuators 40. A single broadband system or unit, designed to operate at pressures up to 1500 psi at 200°F may thus be employed for all models. The same is true for various manufacturers and models of automotive air conditioning systems, automotive power brake systems, and automotive fuel delivery systems. In connection with power brake systems in particular, the invention may be employed to suppress fluid vibrations associated with pulsed operation of anti-skid brake systems, which many drivers do not care to feel at the vehicle brake pedal.

FIGS. 3-6 illustrate various modified embodiments of the invention, in which like reference numerals indicate like components, and like reference numerals with a letter suffix indicate related components. In the system 44 of FIG. 3, sensor 36a is formed as part of piezoelectric actuator 40a, and thus is closely coupled to the actuator during operation. To reduce coupling between actuator 40a and sensor 36a, the sensor material should have a low planar coupling coefficient (such as modified lead titanate), and sensor thickness should be such that its resonant frequency is in the megahertz range. In the system 46 of FIG. 4, the noise vibration electronics is disposed at a right-angle bend in fluid conduit 12a, so that the actuator is approximately axially opposed to the direction of fluid flow. Sensor 36 in FIG. 4

is separate from actuator 40, while sensor 36a in system 48 of FIG. 5 is again closely coupled to actuator 40a.

In system 50 in FIG. 6, piezoelectric actuator 40b is disposed within conduit 12, and is composed of a plurality of annular disks 42b stacked with respect to each other so that the direction of flexure is parallel to the direction of fluid flow through conduit 12. Vibration sensor 36 is coupled to conduit 12 upstream of actuator 40b, and operates through an amplifier 38b to energize actuator 40b 180° out of phase with the highest-amplitude frequency component of the vibrations sensed at sensor 36b. Fluid flows through the hollow interior of actuator 40b formed by the aligned openings of the multiple annular disks 42b.

In one implementation of the present invention in an automotive power steering system and based upon the embodiment of FIG. 2, fluid pressure fluctuations were monitored with PCB Dynamic Pressure Transducers (Type 101A02). The pressure fluctuations were first recorded without any signal being applied to piezoelectric actuator 40. Frequency analysis of this signal was carried out by a Hewlett-Packard Dynamic Signal Analyzer (Model 3562A). To reduce pressure fluctuations or ripple, a phase-shifted pressure field was applied to the hydraulic fluid employing actuator 40. The pressure ripple was again recorded with the Dynamic Pressure Transducer, and frequency analysis was carried out. The amplitudes of the pressure ripples associated with different frequency components observed under these two operating conditions - first without and then with actuation of piezoelectric actuator 40 - were compared to each other. The following table shows a typical set of data for selected dominant frequencies:

	Frequency of pressure ripple (Hz)	Pressure ripple without control (psi)	Pressure ripple with control (psi)
	332.5	0.209	0.137
	665	0.864	0.184
5	997.5	0.122	0.052
	1330	0.370	0.137

It can be seen from the tabulated data that all four frequencies in the pressure ripple were reduced in amplitude. This demonstrates the broadband nature of the invention.

10 In contrast to passive-type pressure-ripple attenuation systems that are sensitive to ripple frequency, the system of the present invention reduces pressure ripples of all frequencies within the given bandwidth. Thus, if one or all of the frequencies were to shift for some reason, their amplitudes would still be reduced by the active attenuation technique of the present invention. The frequency of highest amplitude in this test was at 665 Hz. The
 15 amplitude of the pressure fluctuations was reduced by a factor of five at this dominant frequency. The system is effective at low static pressures as well as high static pressures, as on the order of 1500 psi.

In The Claims:

1.

1 Apparatus for suppressing fluid-borne noise in a fluid conduit (12 or 12a),
2 which comprises:
3 a vibration sensor (36, 36a or 36b) for operative coupling to the conduit to
4 provide an electrical sensor signal as a function of fluid pressure fluctuations in the conduit.
5 a piezoelectric actuator (40, 40a or 40b) adapted to be mounted on the conduit
6 for imparting pressure fluctuations to fluid in the conduit. and
7 an electric controller (38, 38a or 38b) responsive to said sensor signal for
8 energizing said actuator 180° out of phase with fluid pressure fluctuations sensed by said
9 sensor.

2.

1 The apparatus set forth in claim 1 wherein said sensor (36a) is closely coupled
2 to said actuator (40a).

3.

1 The apparatus set forth in claim 1 wherein said sensor (36, 36a or 36b)
2 comprises a piezoelectric sensor.

4.

1 The apparatus set forth in claim 1 wherein said actuator (40, 40a or 40b)
2 comprises a stack of piezoelectric elements (42 or 42b).

5.

1 The apparatus set forth in claim 1 wherein said electronic controller (38, 38a
2 or 38b) is responsive to frequency components of pressure fluctuations of the fluid in the
3 conduit for energizing said actuator (40, 40a or 40b) as a function of amplitude of the
4 frequency component of greatest amplitude.

6.

1 The apparatus set forth in claim 1 wherein said sensor (36, 36a or 36b) is
2 responsive to fluid pressure fluctuations in said conduit over a predetermined frequency range.

7.

1 The apparatus set forth in claim 6 wherein said sensor (36, 36a or 36b) and
2 actuator (40, 40a or 40b) have resonant frequencies greater than said frequency range.

8.

1 The apparatus set forth in claim 7 wherein said frequency range is zero to at
2 least 1000 Hz.

9.

1 The apparatus set forth in claim 1 comprising a unitary assembly (24) having
2 a plug (28) end for removable receipt through an aperture (30) in the conduit.

10.

1 A fluid handling system that comprises:
2 a conduit (12 or 12a) for conducting fluid under pressure, and
3 means for suppressing fluid-borne noise caused by pressure fluctuations in said
4 conduit, including a vibration sensor (36, 36a or 36b) carried by said conduit and operatively
5 coupled to fluid in said conduit for producing an electrical sensor signal as a function of fluid
6 pressure fluctuations in the conduit, a piezoelectric actuator (40, 40a or 40b) mounted on said
7 conduit for imparting pressure fluctuations to fluid in said conduit, and an electronic controller
8 (38, 38a or 38b) responsive to said sensor signal for energizing said actuator 180° out of phase
9 with fluid pressure fluctuations sensed by said sensor.

11.

1 The system set forth in claim 10 wherein said conduit (12) includes a volumetric
2 enlargement (20) to which said sensor (36, 36a or 36b) and actuator (40, 40a or 40b) are
3 coupled.

12.

1 The system set forth in claim 10 wherein said conduit (12a) includes a right-
2 angle turn at which said sensor (36 or 36a) and actuator (40 or 40a) are disposed in opposition
3 to fluid flowing through said conduit.

13.

1 The system set forth in claim 10 wherein said actuator (40, 40a or 40b)
2 comprises at least one annular disk (42 or 42b) disposed within said conduit in such a way that
3 fluid flows through said disk.

14.

1 The system set forth in claim 13 wherein said sensor (36 or 36b) is disposed
2 upstream from said actuator (40 or 40b) with respect to the direction of fluid flow through said
3 conduit.

15.

1 The system set forth in claim 10 wherein said conduit includes an opening (30),
2 and wherein said means is disposed in a unitary assembly (24) removably received in said
3 opening.

16.

1 The system set forth in claim 10 wherein said sensor (36a) is closely coupled
2 to said actuator (40a).

17.

1 The system set forth in claim 10 wherein said sensor (36 or 36b) is spaced from
2 said actuator (40 or 40b).

18.

1 The system set forth in claim 17 wherein said sensor (36 or 36b) is disposed
2 upstream of said actuator (40 or 40b) with respect to the direction of fluid flow through said
3 conduit.

19.

1 The system set forth in claim 10 wherein said sensor (36, 36a or 36b) comprises
2 a piezoelectric sensor.

20.

1 The system set forth in claim 10 wherein said actuator (40, 40a or 40b)
2 comprises a stack of piezoelectric elements (42 or 42b).

21.

1 The system set forth in claim 20 wherein said piezoelectric elements (42b) are
2 of annular flat construction, and are disposed within said conduit (12) in such a way that fluid
3 flows through said elements.

22.

1 The system set forth in claim 10 wherein said electronic controller (38, 38a or
2 38b) is responsive to frequency components of pressure fluctuations of the fluid in the conduit
3 for energizing said actuator (40, 40a or 40b) as a function of amplitude of the frequency
4 component of greatest amplitude.

23.

1 The system set forth in claim 10 wherein said sensor (36, 36a or 36b) is
2 responsive to fluid pressure fluctuations in said conduit over a predetermined frequency range.

24.

1 The system set forth in claim 23 wherein said sensor (36, 36a or 36b) and
2 actuator (40, 40a or 40b) have resonant frequencies greater than said frequency range.

25.

1 The system set forth in claim 24 wherein said frequency range is zero to at least
2 1000 Hz.

26.



1 A method of suppressing fluid-borne noise caused by pressure fluctuations in
2 fluid flowing through a conduit (12 or 12a), which comprises:

3 (a) sensing amplitude and frequency components of pressure fluctuations in the
4 conduit.

5 (b) coupling a piezoelectric actuator (40, 40a or 40b) to said conduit for
6 imparting pressure fluctuations to fluid in the conduit. and

7 (c) energizing said actuator as a function of said amplitude and frequency
8 components.

1/3



2/3




FIG. 3




FIG. 4

3/3




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/11738

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61F 11/06

US CL : 381/71.5

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 381/71.5, 71.1, 71.2, 71.3, 71.4

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,493,615 A (BURKE ET AL) 20 FEBRUARY 1996, ABSTRACT AND FIGS. 1-5.	1-26

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

31 JULY 1998

Date of mailing of the international search report

14 OCT 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231
Facsimile No. (703) 305-3230

Authorized officer

VIVIAN CHANG

Telephone No. (703) 308-6739

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/02210

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H01F27/33

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHEDMinimum documentation searched (classification system followed by classification symbols)
IPC 7 H01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 726 617 A (SMITH STEPHEN LINWOOD ET AL) 10 March 1998 (1998-03-10) claims 1-10 ---	1, 10, 11
Y	US 5 333 455 A (YOSHIOKA SHIGEKI) 2 August 1994 (1994-08-02) column 3, line 25 -column 5, line 20 ---	1, 10, 11
A	PATENT ABSTRACTS OF JAPAN vol. 004, no. 092 (M-018), 3 July 1980 (1980-07-03) & JP 55 049273 A (CANON INC), 9 April 1980 (1980-04-09) abstract ---	
A	WO 81 01479 A (SOUND ATTENUATORS LTD ;CHAPLIN G (GB); BEARCROFT R (GB); SMITH R () 28 May 1981 (1981-05-28) --- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 July 2000

Date of mailing of the international search report

18/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vanhulle, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/02210

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 55060 A (ECHLIN INC ;KUMAR DEVENDRA (US); KUMAR SATYENDRA (US); DOUGHERTY M) 10 December 1998 (1998-12-10) ---	
A	GB 897 859 A (ASSOCIATED ELECTRICAL INDUSTRIES LTD.) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/02210

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5726617	A	10-03-1998	NONE	
US 5333455	A	02-08-1994	JP 5087189 A DE 4232225 A	06-04-1993 01-04-1993
JP 55049273	A	09-04-1980	JP 1288932 C JP 60010912 B	14-11-1985 20-03-1985
WO 8101479	A	28-05-1981	AU 6481380 A EP 0041954 A	03-06-1981 23-12-1981
WO 9855060	A	10-12-1998	AU 8060498 A	21-12-1998
GB 897859	A		NONE	

Patent Abstracts of Japan

PUBLICATION NUMBER : 55049273
PUBLICATION DATE : 09-04-80


APPLICATION DATE : 04-10-78
APPLICATION NUMBER : 53122338

APPLICANT : CANON INC;

INVENTOR : KYOGOKU HIROSHI;

INT.CL. : B41J 3/04

TITLE : RECORDING HEAD



ABSTRACT : PURPOSE: To obtain a recording head of small size, low power consumption and low noise, which is designed capable of supplying liquid with high efficiency, of discharging liquid with high efficiency and of recording in response to electrical signal of high frequency satisfactorily, by making it possible to conduct pressure to the liquid under a specified condition.

CONSTITUTION: A recording medium liquid flow passage 2, a discharge orifice 3, No. 1 chamber 4 connected to the orifice 3, No. 2 chamber 6 connected to the passage 2 through connecting passages 5 and 10, and No. 3 chamber 9 connected to the passage 2 through a connecting passage 8 are provided. A pressure means 7 constitutes a part of wall surface of the chambers 4 and 6 and causes pressure wave into a liquid in the chamber 4. An electric impulse is given between 2 lead electrodes 12 to deflect a piezo-electricity element 1 and connect the chamber 4 with the chamber 6 to quickly supply the liquid corresponding to increase in volume. By removing the electric impulse, volume of the chamber 4 is reduced momentarily, pressure wave is generated in the liquid contained in the chamber 4 and drops of the liquid are jetted out from the orifice 3.

COPYRIGHT: (C)1980,JPO&Japio